

:: Driver: Team Associated **:: Date:** _____
:: Track: Standard RC8B FT Setup
:: Event: _____

Setup Sheet for Team Associated's RC8B

Rev. 1

:: Front Suspension

anti-roll bar:

- ☐ 2.2 - black
☒ 2.5 - silver
☐ 2.8 - gold

bump-steer
washers:
0
 out

upper hinge pin bushing

front # 2 rear # 1

☒ up ☐ down ☐ up ☐ down

camber: 2 °

caster: 16 °

toe: 0 °

ride height: 29mm

kickup bushing
 # 2
☒ up ☐ down

:: Rear Suspension

anti-roll bar:

- ☐ 2.2 - black
☒ 2.5 - silver
☐ 2.8 - gold

wheelbase:

- ☐ long
☒ medium
☐ short

camber: 2 °

toe bushing
d-plate:
 # 1
☐ in ☐ out

hub:
 upper
 lower

ride height: 30mm

squat bushing
c-plate:
 # 2
☐ up ☒ down

:: Front Shocks

spring: bronze piston: 6x1.3mm
 shock fluid: 25wt. length: 109mm
 shock cap: aluminum rebound: full

:: Rear Shocks

spring: black piston: 6x1.3mm
 shock fluid: 25wt. length: 126mm
 shock cap: aluminum rebound: full

:: Chassis Braces / Wheel Hex

chassis braces:
☐ pivot ☒ molded ☐ aluminum
 wheel hex:
☒ standard ☐ narrow

:: Steering Blocks

steering blocks:
☒ standard
☐ cnc FT knuckles

:: Rear Hubs

rear hubs:
☒ standard
☐ cnc FT hubs

:: Differentials

front fluid: 5R
 center fluid: 5R
 rear fluid: 5R

:: Wing

location: ☒ forward ☐ back
 angle: ☒ low ☐ med. ☐ high
 type: al gap: _____

:: Gearing/Clutch

gearing: 16 / 44
 clutch shoes: aluminum
 clutch spring: ☐ .9mm ☒ 1.0mm ☐ 1.1mm

:: Engine

engine: _____ restrictor: _____
 muffler: _____ temp: _____
 glow plug: _____
 fuel: _____

:: Tires

tire (F/R): _____ / _____
 compound (F/R): _____ / _____
 insert: _____ wheel: FT 83mm
 traction additive: _____

:: Race and Vehicle Comments

qualify: _____ main: _____ finish: _____ tq: ☐
 comments: _____

:: Track Info

smooth: ☐ bumpy: ☐ blue groove: ☐
 traction: ☐ high ☐ med. ☐ low
 soft dirt: ☐ grass: ☐ clay: ☐ wet: ☐
 dusty: ☐ other: _____

