

Setup Sheet for Team Associated's RC8B

RESET FIELDS

Rev. 1

:: Front Suspension

anti-roll bar:

- ☐ 2.2 - black
☒ 2.5 - silver
☐ 2.8 - gold

bump-steer washers:
 1 _____
 out

upper hinge pin bushing

front # 2 _____ rear # 1 _____

☒ up ☐ down ☐ up ☐ down

camber: -2 °

caster: 16 °

toe: -2 °

kickup bushing

2 _____

☒ up ☐ down

ride height: 29 mm

:: Rear Suspension

anti-roll bar:

- ☐ 2.2 - black
☒ 2.5 - silver
☐ 2.8 - gold

wheelbase:

- ☐ long
☒ medium
☐ short

camber: -2 °

toe bushing d-plate:

1 _____

☐ in ☐ out

hub:
 upper
 lower

ride height: 30 mm

squat bushing c-plate:

1 _____

☐ up ☐ down

:: Front Shocks

spring: Bronze piston: 10 x 1.1 Tapered
 shock fluid: 30 wt length: 108.5 mm
 shock cap: Stock rebound: 3 mm

:: Rear Shocks

spring: Silver piston: 10 x 1.1 Tapered
 shock fluid: 27.5 wt Mixed length: 126.75
 shock cap: Stock rebound: 5 mm

:: Chassis Braces / Wheel Hex

chassis braces:
☐ pivot ☒ molded ☐ aluminum
 wheel hex:
☒ standard ☐ narrow

:: Steering Blocks

steering blocks:
☐ standard
☒ cnc FT knuckles

:: Rear Hubs

rear hubs:
☐ standard
☒ cnc FT hubs

:: Differentials

front fluid: 5000
 center fluid: 5000
 rear fluid: 5000

:: Wing

location: ☒ forward ☐ back
 angle: ☒ low ☐ med. ☐ high
 type: MP9 gap: 25 mm

:: Gearing/Clutch

gearing: 16 / 44
 clutch shoes: Hard Aluminum
 clutch spring: ☐ .9mm ☒ 1.0mm ☐ 1.1 mm

:: Engine

engine: Orion Alpha restrictor: 7 mm
 muffler: Orion 2013 temp: 260
 glow plug: Orion Hot
 fuel: Sidewinder 30%

:: Tires

tire (F/R): Proline Cut Hoeshots / Proline Cut Hoeshots
 compound (F/R): M3 / M3
 insert: Stock Gray wheel: Associated 83 mm
 traction additive: N/A

:: Race and Vehicle Comments

qualify: 2 main: A finish: 1 tq: ☐

comments: _____

:: Track Info

smooth: ☐ bumpy: ☒ blue groove: ☐
 traction: ☐ high ☒ med. ☐ low
 soft dirt: ☐ grass: ☐ clay: ☒ wet: ☒
 dusty: ☐ other: _____

